

**SCHOOL DISTRICT NO. 50 (HAIDA GWAII) INVITATION TO BID
GUDANGAAY TLAATS'GAA NAAY SCHOOL WINDOW AND DOOR REPLACEMENT**
Tenders are invited by School District No. 50 (Haida Gwaii) for window and door replacement in Masset, B.C.

The scope of work includes installing 6 new commercial storm front doors and all hardware associated with said doors, installation of 31 triple glazed vinyl windows. The interior liners for the windows will be pine with a clear finish. The interior trim will be 2" wide beveled stock painted brown. Color to be determined upon successful tender. All work will be done to the latest BC Building code. All doors and windows to be replaced will be supplied by School District 50. Due to unknown factors some window and door openings may need some modification. Asbestos is a known component in the building of Gudangaay Tlaats'gaa Naay School and any and all work with it must follow WCB regulations. No work shall commence until the Asbestos manual is read and understood, which will be supplied by School District 50.

The project will begin immediately following a successful tendering process and must reach substantial completion by August 31, 2017.

The site is located at 1647 Cook Street, Masset, BC.

A site visit is greatly encouraged for general contractors intending to bid.

Contact Lao Peerless (250) 559-8471 Ext 107 or lpeerless@sd50.bc.ca

Contractors must provide School District No.50 with their WorkSafeBC Number and must provide proof of liability insurance up to \$ 2 million.

All tenders must be provided to School District office located at

107 3rd Ave.
Queen Charlotte, BC
V0T 1S0

in a sealed envelope by no later than 3:00pm June 23, 2017
(according to the School District office's timekeeping system).

Tenders are to remain irrevocable for a period of sixty (60) days following the bid closing. Bids will be opened in the School District No. 50 (Haida Gwaii) District Office following the tender closing time. The lowest, or any tender, will not be necessarily accepted and the School District reserves the right to reject any and all tenders.

All tender inquiries shall be addressed to:

Lao Peerless
Maintenance Supervisor
(250) 559-8471 Ext 107

GUDANGAAY TLAATS'GAA NAA Y SCHOOL
WINDOW AND DOOR REPLACEMENT 1647 Cook Street, Masset, BC
School District No.50 (Haida Gwaii)
lpeerless@sd50.bc.ca

BID FORM

Project Name: GUDANGAAY TLAATS'GAA NAA Y SCHOOL Windows and Doors

Address: 1647 Cook Street, Masset, BC

Closing Date: 3:00pm June 23, 2017

Submission of Bids by Email to:

School District No.50 (Haida Gwaii) Attention: Lao Peerless, Maintenance Supervisor
Email: lpeerless@sd50.bc.ca

Send Queries to:

School District No.50 (Haida Gwaii) Attention: Lao Peerless, Maintenance Supervisor
Email: lpeerless@sd50.bc.ca

CONTRACTORS NAME _____

CONTRACTORS PHONE NUMBER _____

CONTRACTORS ADDRESS _____

CONTRACT PRICE INCLUDING TAXES _____

CONTRACTORS SIGNATURE _____

DATE _____

TRICON

TRUSS & MILLWORK LTD

sales@tricontruss.ca
 ph.250.847.2117 fax.250.847.9035

QUOTE

Name: School District #50
 Quote No.: 18029
 Phone: (250) 559-8471
 Fax:
 Email: mjones@sd50.bc.ca
 Date: May 25, 2017
 Quoted By: Plug, Michael

Qnt	Unit	Description	Price	Amount
1	EA	<ul style="list-style-type: none"> - Adams-Rite #8600 Series Concealed Vertical Rod Panic Hardware for Both Doors, w/ 6-Pin Keyed Schlage Cylinder for RHR Door - Offset D-Pull for (1) Door in Each Pair - Global #4300 Closers <p>[Unit #5, Music Room] Aluminum #2050 Series Storefront Double Door Unit, RO: 64 1/2" x 82 1/4"</p> <ul style="list-style-type: none"> - Pair of 30" x 80" Doors, #350 Series (Medium Stile) - Clear Anodized, Thermally Broken Aluminum Frame - Aluminum Threshold - Full Length, LowE/Argon Dual Pane Glazing - Doors Swing Out on Pivot Hinges - Adams-Rite #8600 Series Concealed Vertical Rod Panic Hardware for Both Doors, w/ 6-Pin Keyed Schlage Cylinder for RHR Door - Offset D-Pull for Each Door - Ditek Entrematic Cast Housing HA-8P Simultaneous Automatic Opener for Both Slabs, w/ 2 Push Buttons <p>** Note that panic hardware will need to be dogged for automatic opener to work.</p>		
1	EA	<p>[Unit #6, Smoking Pit] Aluminum #2050 Series Storefront Double Door Unit, RO: 75" x 85"</p> <ul style="list-style-type: none"> - Pair of 35 1/4" x 82 3/4" Doors, #350 Series (Medium Stile) - Clear Anodized, Thermally Broken Aluminum Frame - Aluminum Threshold - Full Length, LowE/Argon Dual Pane Glazing - Doors Swing Out on 1.5 Pairs of 4" x 4 1/2" Stainless Steel Butt hinges - Adams-Rite #8600 Series Concealed Vertical Rod Panic Hardware for Both Doors, w/ 6-Pin Keyed Schlage Cylinder for RHR Door - Offset D-Pull for Each Door - Global #4300 Closers <p>Notes: 1. F.O.B. Tricon</p> <p>Subtotal: GP - GST 5%, PST 7% GST/HST PST</p>		
Comments			Continued...	



TRICON

TRUSS & MILLWORK LTD

sales@tricontruss.ca
 ph.250.847.2117 fax.250.847.9035

QUOTE

Name: School District #50
 Quote No.: 18029
 Phone: (250) 559-8471
 Fax:
 Email: mjones@sd50.bc.ca
 Date: May 25, 2017
 Quoted By: Plug, Michael

Qnt	Unit	Description	Price	Amount
1	EA	<p>[Unit #1, Main Entrance] Aluminum #2050 Series Storefront Double Door Unit, RO: 74 1/2" x 84" - Pair of 35" x 81 3/4" Doors, #350 Series (Medium Stile) - Clear Anodized, Thermally Broken Aluminum Frame - Aluminum Threshold - Full Length, LowE/Argon Dual Pane Glazing - Doors Swing Out on 1.5 Pairs of 4" x 4 1/2" Stainless Steel Butt hinges - Adams-Rite #8600 Series Concealed Vertical Rod Panic Hardware for Both Doors, w/ 6-Pin Keyed Schlage Cylinder for RHR Door - Offset D-Pull for Each Door - Ditek Entrematic Cast Housing HA-8P Automatic Opener for One Slab, w/ 2 Push Buttons - Global #4300 Closer for One Slab ** Note that panic hardware will need to be dogged for automatic opener to work.</p>		
1	EA	<p>[Unit #2, Side Entry] Aluminum #2050 Series Storefront Sidelite Double Door Sidelite Unit, RO: 91" x 84" - Pair of 36" x 81 3/4" Doors, #350 Series (Medium Stile) - Clear Anodized, Thermally Broken Aluminum Frame - Aluminum Threshold - Full Length, LowE/Argon Dual Pane Glazing - Doors Swing Out on 1.5 Pairs of 4" x 4 1/2" Stainless Steel Butt hinges - Adams-Rite #8600 Series Concealed Vertical Rod Panic Hardware for Both Doors, w/ 6-Pin Keyed Schlage Cylinder for RHR Door - Offset D-Pull for Each Door - Ditek Entrematic Cast Housing HA-8P Automatic Opener for One Slab, w/ 2 Push Buttons - Global #4300 Closer for One Slab ** Note that panic hardware will need to be dogged for automatic opener to work.</p>		
2	EA	<p>[Unit #3 & 4, Library] Aluminum #2050 Series Storefront Double Door Unit, RO: 75 1/2" x 86 1/2" - Pair of 35 1/2" x 84 1/2" Doors, #350 Series (Medium Stile) - Clear Anodized, Thermally Broken Aluminum Frame - Aluminum Threshold - Full Length, LowE/Argon Dual Pane Glazing - Doors Swing Out on 1.5 Pairs of 4" x 4 1/2" Stainless Steel Butt hinges</p>		
Comments			Continued...	





Customer Quote

QUOTE NUMBER: SQFHI000958-2

QUOTE NAME: Window Quote Fully Enclosed Crating HS4V

PURCHASE ORDER:

SUPPLIER:
 Tricon Truss & Millwork (Builder)
 3516 Fulton Avenue

 Smithers BC V0J 2N0
Phone: 250-847-2117
Fax: 250-847-9035

SALES CONTACT:
 Kevin Plug
Phone:
Mobile:
Fax:
E-mail:
 sales@tricontruss.ca

CLIENT:
 School District 50

Phone: 250-637-1705 (Lao Peerless)
Fax:

SHIP TO:
 Same as Bill-to

SHIP TO CONTACT:

Phone:
Mobile:
Fax:
E-mail:

Created Date: 5/5/2017 4:55:15 PM
Ordered Date:
Requested Date:

Phone:
Fax:
Email:

CORE ORDER NUMBER:


COMMENTS


LINE#	QTY	PRODUCT DESCRIPTION	PRICING	TOTALS
1	3	Slider / Single Hung / Picture Room Location: W1: Office Series: 7100 Horizon - Single Overall Dimensions OSM Frame: 91W x 28H RO: 92W x 29H Unit Information Row 1 - Unit 1: 91" W (Custom) x 28" H (Custom) - OFO Options Glazing: HS4V (SunStop / Low-E) with Argon Grilles: No Grille Colour: Exterior: White / Interior: White Interior Options: 3 3/8" / White / PVC Exterior Options: Frame - Nail Fin Hardware: White Screen: White Screen / Included Crating: C - Completely Enclosed Energy Star Row 1 - Unit 1: Zone 1, 2 / Energy Rating: 25 / U-Value: 1.42 (Metric/SH) 0.25 (US/IMP) / SHGC: 0.26 / CPD: AWW-A-00-00000-00001 NBC 2010 SEC. 9.36 All Units: Qualifying Zone(s): 4, 5, 6, 7A This Unit does NOT meet Egress as Defined by the 2010 Canadian National Building Code.	Customer	



All windows and doors are viewed from the exterior

COMMENTS

LINE#	QTY	PRODUCT DESCRIPTION	PRICING	TOTALS
2	2	Casement / Awning / Picture / Fixed Room Location: W2, Office Series: 2500 Energy Saver - Single Overall Dimensions OSM Frame: 27W x 24H RO: 28W x 25H Unit Information Row 1 - Unit 1: 27" W (Custom) x 24" H (Custom) - Picture Options Glazing: HS4V (SunStop / Low-E) with Argon Grilles: No Grille Colour: Exterior: White / Interior: White Interior Options: 2 L/B" / White / PVC Exterior Options: Frame - Nail Fin Hardware: Crating: C - Completely Enclosed Energy Star Row 1 - Unit 1: Zone: 1.2 / Energy Rating: 31 / U-Value: 1.25 (Metric/SH) / 0.22 (US / I/P) / SHGC: 0.31 / CPD: AWW-A-29-00123-00001 NBC 2010 SEC. 9.36 All Units: Qualifying Zone(s): 4, 5, 6, 7A, 7B, 8	Customer:	
RO: 28W x 25H OSM: 27W x 24H  All windows and doors are viewed from the exterior				
COMMENTS				


LINE#	QTY	PRODUCT DESCRIPTION	PRICING	TOTALS
3	1	Slider / Single Hung / Picture Room Location: W3, Office Series: 7100 Horizon - Single Overall Dimensions OSM Frame: 61W x 28H RO: 62W x 29H Unit Information Row 1 - Unit 1: 61" W (Custom) x 28" H (Custom) - L-R Options Glazing: HS4V (SunStop / Low-E) with Argon Grilles: No Grille Colour: Exterior: White / Interior: White Interior Options: 3.3/B" / White / PVC Exterior Options: Frame - Nail Fin Hardware: White Screen: White Screen / Included Crating: C - Completely Enclosed Energy Star Row 1 - Unit 1: Zone: 1.2 / Energy Rating: 25 / U-Value: 1.12 (Metric/SH) / 0.25 (US / I/P) / SHGC: 0.28 / CPD: AWW-A-00-00000-00001 NBC 2010 SEC. 9.36 All Units: Qualifying Zone(s): 4, 5, 6, 7A	Customer:	
RO: 62W x 29H OSM: 61W x 28H  All windows and doors are viewed from the exterior				
COMMENTS				





Customer Quote


QUOTE NUMBER: SQFHI000958-2

LINE#	QTY	PRODUCT DESCRIPTION	PRICING	TOTALS
4	6	<p>Casement / Awning / Picture / Fixed</p> <p>Room Location: W4, Science Room Series: 2500 Energy Saver - 1W x 2H</p> <p>Overall Dimensions OSM Frame: 34 1/4W x 52 1/4H RO: 35 1/4W x 53 1/4H</p> <p>Unit Information Row 1 - Unit 1: 34 1/4" W (Custom) x 17 3/8" H (Custom) - Awning Row 2 - Unit 1: 34 1/4" W (Custom) x 31 3/4" H (Custom) - Picture</p> <p>Options Glazing: HS4V (SunStop / Low-E) with Argon Grilles: No Grille Colour: Exterior: White / Interior: White Interior Options: 2 1/8" / White / PVC Exterior Options: Frame - Nail Fin Hardware: Encore / Folding / White Screen: White Screen / Included Crating: C - Completely Enclosed</p> <p>Energy Star Row 1 - Unit 1: Zone 1 2 / Energy Rating 25 / U-Value 1.31 (Metric/SI) 0.23 (U.S./I-P) / SHGC: 0.24 / CPD AWW-A-11-00123-00001 Row 2 - Unit 1: Zone 1 2 / Energy Rating 31 / U-Value 1.25 (Metric/SI) 0.22 (U.S./I-P) / SHGC: 0.31 / CPD AWW-A-29-00123-00001</p> <p>NBC 2010 SEC. 9.36 All Units: Qualifying Zone(s) 4, 5, 6, 7A, 7B, 8</p> <p>Units 1 do NOT meet Egress as Defined by the 2010 Canadian National Building Code.</p>	Customer:	
<p>RO: 35 1/4W x 53 1/4H OSM: 34 1/4W x 52 1/4H</p> <p>All windows and doors are viewed from the exterior</p>				
COMMENTS				


LINE#	QTY	PRODUCT DESCRIPTION	PRICING	TOTALS
5	1	Casement / Awning / Picture / Fixed Room Location: W5; Staff Room Series: 2500 Energy Saver - Single Overall Dimensions OSM Frame: 28W x 46H RO: 29W x 47H Unit Information Row 1 - Unit 1: 28" W (Custom) x 46" H (Custom) - Awning Options Glazing: HS IV (SunStop / Low-E) with Argon Grilles: No Grille Colour: Exterior White / Interior: White Interior Options: 2 1/8" / White / PVC Exterior Options: Frame - Nail Fin Hardware: Encore / Folding / White Screen: White Screen / Included Crating: C - Completely Enclosed Energy Star Row 1 - Unit 1 Zone 1 2 / Energy Rating 25 / 10Value: 1.31 (Metric/SI) 0.23 (US/IEP) / SHGC: 0.24 / U-PD: AWWA-11-00125-09001 NBC 2010 SEC. 9.36 All Units: Qualifying Zone(s): 4, 5, 6, 7A, 7B, 8 This Unit does NOT meet Egress as Defined by the 2010 Canadian National Building Code.	Customer:	
RO: 29W x 47H OSM: 28W x 46H 		All windows and doors are viewed from the exterior		
COMMENTS				

LINE#	QTY	PRODUCT DESCRIPTION	PRICING	TOTALS
6	2	<p>Casement / Awning / Picture / Fixed</p> <p>Room Location: W6, AV Room Series: 2500 Energy Saver - 1W x 2H</p> <p>Overall Dimensions OSM Frame: 38W x 67H RO: 39W x 68H</p> <p>Unit Information Row 1 - Unit 1: 38" W (Custom) x 22 9/32" H (Custom) - Awning Row 2 - Unit 1: 38" W (Custom) x 11 19/32" H (Custom) - Picture</p> <p>Options Glazing: HS4V (SunStop / Low-E) with Argon Grilles: No Grille Colour: Exterior: White / Interior: White Interior Options: 2 1/8" / White / PVC Exterior Options: Frame - Nail Fin Hardware: Encore / Folding / White Screen: White Screen / Included Crating: C - Completely Enclosed</p> <p>Energy Star Row 1 - Unit 1 Zone: 1 2 / Energy Rating: 25 / U Value: 1.31 (Metric/SI) 0.23 (U.S./I-P) / SHGC: 0.24 / CPD: AWW-A-11-00123-00001 Row 2 - Unit 1 Zone: 1 2 / Energy Rating: 31 / U Value: 1.25 (Metric/SI) 0.22 (U.S./I-P) / SHGC: 0.31 / CPD: AWW-A-29-00123-00001</p> <p>NBC 2010 SEC. 9.36 All Units: Qualifying Zone(s): 4, 5, 6, 7A, 7B, 8</p> <p>Units 1 do NOT meet Egress as Defined by the 2010 Canadian National Building Code.</p>	Customer:	
<p>RO: 39W x 68H OSM: 38W x 67H</p>  <p>All windows and doors are viewed from the exterior</p>				
COMMENTS				

LINE#	QTY	PRODUCT DESCRIPTION	PRICING	TOTALS
7	4	Slider / Single Hung / Picture Room Location: W7, Home Ec, Kitchen, Lunch Room Series 7100 Horizon - Single Overall Dimensions OSM Frame: 46 1/2W x 34 1/2H RO: 47 1/2W x 35 1/2H Unit Information Row 1 - Unit 1: 46 1/2" W (Custom) x 34 1/2" H (Custom) - OF Options Glazing: 11S1V (SunStop / Low-E) with Argon Grilles: No Grille Colour: Exterior: White / Interior: White Interior Options: 3 3/8" / White / PVC Exterior Options: Frame - Nail Fin Hardware: White Screen: White Screen / Included Crating: C - Completely Enclosed Energy Star Row 1 - Unit 1: Zone 1.2 / Energy Rating 25 / U-Value 1.12 (Metric/St) 0.25 (US /I-P) / SHGC 0.20 / CPD: AWW-A-90-00003-00001 NBC 2010 SEC. 9.36 All Units: Qualifying Zone(s): 1, 5, 6, 7A	Customer:	
RO: 47 1/2W x 35 1/2H OSM: 46 1/2W x 34 1/2H 		All windows and doors are viewed from the exterior		
COMMENTS				


LINE#	QTY	PRODUCT DESCRIPTION	PRICING	TOTALS
8	8	<p>Casement / Awning / Picture / Fixed</p> <p>Room Location: WB; Room 22-23 Series: 2500 Energy Saver - 1W x 2H</p> <p>Overall Dimensions OSM Frame: 28 1/4W x 52 1/4H RO: 29 1/4W x 53 1/4H</p> <p>Unit Information Row 1 - Unit 1: 28 1/4" W (Custom) x 17 3/8" H (Custom) - Awning Row 2 - Unit 1: 28 1/4" W (Custom) x 34 3/4" H (Custom) - Picture</p> <p>Options Glazing: HS4V (SunStop / Low-E) with Argon Grilles: No Grille Colour: Exterior: White / Interior: White Interior Options: 2 1/8" / White / PVC Exterior Options: Frame - Nail Fin Hardware: Encore / Folding / White Screen: White Screen / Included Crating: C - Completely Enclosed</p> <p>Energy Star Row 1 - Unit 1, Zone: 1.2 / Energy Rating 25 / U-Value: 1.31 (Metric/SI) 0.23 (U.S./I-P) / SHGC: 0.24 / CPD: AWW-A-11-00123-00001 Row 2 - Unit 1, Zone: 1.2 / Energy Rating 31 / U-Value: 1.25 (Metric/SI) 0.22 (U.S./I-P) / SHGC: 0.31 / CPD: AWW-A-29-00123-00001</p> <p>NBC 2010 SEC. 9.36 All Units: Qualifying Zone(s): 4, 5, 6, 7A, 7B, 8</p> <p>Units 1 do NOT meet Egress as Defined by the 2010 Canadian National Building Code.</p>	Customer:	
		<p>RO: 29 1/4W x 53 1/4H</p> <p>OSM: 28 1/4W x 52 1/4H</p>  <p>All windows and doors are viewed from the exterior</p>		
COMMENTS				


LINE#	QTY	PRODUCT DESCRIPTION	PRICING	TOTALS
9	1	Slider / Single Hung / Picture Room Location: W9; Storage Series 7100 Horizon - Single Overall Dimensions OSM Frame: 62W x 27 1/2H RO: 63W x 28 1/2H Unit Information Row 1 - Unit 1: 62" W (Custom) x 27 1/2" H (Custom) - OF Options Glazing: HS1V (SunStop / Low-E) with Argon Grilles: No Grille Colour: Exterior: White / Interior: White Interior Options: 3 3/8" / White / PVC Exterior Options: Frame - Nail Fin Hardware: White Screen: White Screen / Included Crating: C - Completely Enclosed Energy Star Row 1 - Unit 1 Zone 1 2 / Energy Rating 25 / U-Value: 1.42 (Metric/ST) 0.25 (HS / E-P) / SHGC: 0.20 / CPD: AW-W-A-90-00000-00001 NBC 2010 SEC. 9.36 All Units: Qualifying Zone(s): 4, 5, 6, 7A This Unit does NOT meet Egress as Defined by the 2010 Canadian National Building Code.	Customer:	




All windows and doors are viewed from the exterior

COMMENTS

LINE#	QTY	PRODUCT DESCRIPTION	PRICING	TOTALS
10	1	<p>Casement / Awning / Picture / Fixed</p> <p>Room Location: W10, Office Series: 2500 Energy Saver - 1W x 2H</p> <p>Overall Dimensions OSM Frame: 31 1/2W x 54H RO: 32 1/2W x 55H</p> <p>Unit Information Row 1 - Unit 1: 31 1/2" W (Custom) x 17 31/32" H (Custom) - Awning Row 2 - Unit 1: 31 1/2" W (Custom) x 35 29/32" H (Custom) - Picture</p> <p>Options Glazing: HS-1 (SunStop / Clear) with Argon Custom Glazing: Window 1 : Textured Glass - Inboard Obscure, Thickness(Outboard/Inboard): 3mm/3mm Window 2 : Thickness(Outboard/Inboard): 3mm/3mm Grilles: No Grille Colour: Exterior: White / Interior: White Interior Options: 2 1/8" / White / PVC Exterior Options: Frame - Nail Fin Hardware: Encore / Folding / White Screen: White Screen / Included Crating: C - Completely Enclosed</p> <p>Energy Star Row 1 - Unit 1 Zone 1 / Energy Rating 21 / U-Value: 1.48 (Metric/SI) 0.26 (U.S./I-P) / SHGC: 0.24 / CPD: AWW-A-11-00119-00001 Row 2 - Unit 1 Zone 1 / Energy Rating 26 / U-Value: 1.48 (Metric/SI) 0.26 (U.S./I-P) / SHGC: 0.32 / CPD: AWW-A-29-00119-00001</p> <p>NBC 2010 SEC. 9.36 All Units: Qualifying Zone(s) 4, 5, 6, 7A</p> <p>Units 1 do NOT meet Egress as Defined by the 2010 Canadian National Building Code.</p>	Customer:	
<p>RO: 32 1/2W x 55H OSM: 31 1/2W x 54H</p>  <p>All windows and doors are viewed from the exterior</p>				
<p>COMMENTS Awning section with Obscure glass</p>				

LINE#	QTY	PRODUCT DESCRIPTION	PRICING	TOTALS
11	1	Casement / Awning / Picture / Fixed Room Location: W11; Storage by Office Series: 2500 Energy Saver - 2W x 2H Overall Dimensions OSM Frame: 68W x 54H RO: 69W x 55H Unit Information Row 1 - Unit 1: 33 29/32" W (Custom) x 17 31/32" H (Custom) - Awning Row 1 - Unit 2: 33 29/32" W (Custom) x 17 31/32" H (Custom) - Awning Row 2 - Unit 1: 33 29/32" W (Custom) x 35 29/32" H (Custom) - Picture Row 2 - Unit 2: 33 29/32" W (Custom) x 35 29/32" H (Custom) - Picture Options Glazing: HSI (SunStop / Clear) with Argon Custom Glazing: All Sealed Units: Textured Glass - Inboard; Obscure; Thickness (Outboard/Inboard) 3mm/3mm Grilles: No Grille Colour: Exterior: White / Interior: White Interior Options: 2 1/8" / White / PVC Exterior Options: Frame - Nail Fin Hardware: Encore / Folding / White Screen: White Screen / Included Crating: C - Completely Enclosed Energy Star Row 1 - Unit 1: Zone 1 / Energy Rating: 24 / U-Value: 1.48 (Metric/SI) 0.26 (U.S./I-P) / SHGC: 0.24 / CPD: AWW-A-11-00119-00001 Row 1 - Unit 2: Zone 1 / Energy Rating: 21 / U-Value: 1.40 (Metric/SI) 0.26 (U.S./I-P) / SHGC: 0.24 / CPD: AWW-A-11-00119-00001 Row 2 - Unit 1: Zone 1 / Energy Rating: 26 / U-Value: 1.48 (Metric/SI) 0.26 (U.S./I-P) / SHGC: 0.32 / CPD: AWW-A-29-00119-00001 Row 2 - Unit 2: Zone 1 / Energy Rating: 26 / U-Value: 1.48 (Metric/SI) 0.26 (U.S./I-P) / SHGC: 0.32 / CPD: AWW-A-29-00119-00001 NBC 2010 SEC. 9.36 All Units: Qualifying Zone(s): 4, 5, 6, 7A Units 1,2 do NOT meet Egress as Defined by the 2010 Canadian National Building Code.	Customer:	
RO: 69W x 55H OSM: 68W x 54H 		All windows and doors are viewed from the exterior		
COMMENTS				
All sealed units with Obscure glass				

LINE#	QTY	PRODUCT DESCRIPTION	PRICING	TOTALS
12	2	<p>Casement / Awning / Picture / Fixed</p> <p>Room Location: W12, Med Room & Plant room Series: 2500 Energy Saver - 1W x 2H</p> <p>Overall Dimensions OSM Frame: 28 1/2" W x 54" H RO: 29 1/2" W x 55" H</p> <p>Unit Information Row 1 - Unit 1: 28 1/2" W (Custom) x 17 31/32" H (Custom) - Awning Row 2 - Unit 1: 28 1/2" W (Custom) x 35 29/32" H (Custom) - Picture</p> <p>Options Glazing: IIS4 (SunStop / Clear) with Argon Custom Glazing: All Sealed Units: Textured Glass - Inboard, Obscure, Thickness (Outboard/Inboard): 3mm/3mm Grilles: No Grille Colour: Exterior White / Interior White Interior Options: 2 1/8" / White / PVC Exterior Options: Frame - Nail Fin Hardware: Encore / Folding / White Screen: White Screen / Included Crating: C - Completely Enclosed</p> <p>Energy Star Row 1 - Unit 1: Zone 1 / Energy Rating: 21 / U-Value: 1.48 (Metric/SI) / 0.26 (U.S./I-P) / SHGC: 0.21 / CPD: AWW-A-11-00119-00001 Row 2 - Unit 1: Zone: 1 / Energy Rating: 26 / U-Value: 1.48 (Metric/SI) / 0.26 (U.S./I-P) / SHGC: 0.32 / CPD: AWW-A-29-00119-00001</p> <p>NBC 2010 SEC. 9.36 All Units: Qualifying Zone(s): 4, 5, 6, 7A</p> <p>Units 1 do NOT meet Egress as Defined by the 2010 Canadian National Building Code.</p>	Customer:	
<p>RO: 29 1/2" W x 55" H OSM: 28 1/2" W x 54" H</p>  <p>All windows and doors are viewed from the exterior</p>				
<p>COMMENTS All sealed units with Obscure glass.</p>				



Customer Quote

QUOTE NUMBER: SQFHI000958-2

QUOTE NAME: Window Quote, Fully Enclosed Crating, HS4V

CLIENT:

Subtotal

Adjusted Subtotal

Freight

Freight Subtotal

GST

PST

Total

SUBMITTED BY: _____

ACCEPTED BY: _____

DATE: _____

DISCLAIMER 1. This quotation is valid for 30 days unless otherwise stated in writing, and is subject to product change and availability. If this quotation contains items with zero dollars it is considered to be incomplete. 2. A purchase order referencing this quotation number or an authorized signed copy of this quotation confirms acceptance of the details contained within this quotation. 3. Verbal agreements and representations made by All Weather Windows (AWW) sales staff will not be accepted and will not form part of this quotation. 4. Product pricing is FOB All Weather Window's Edmonton or Mississauga Plant unless otherwise stated. 5. All applicable freight charges and taxes are extra including AWW's standard freight charge where applicable. 6. Acceptance of this order based on this quotation is subject to normal credit approval. 7. All Weather Windows Product Warranty is outlined and stated in the approved AWW Warranty Guide. 8. Production lead times start from the approval date of this quotation. Production lead times are used to estimate the delivery of the product and AWW will not be held financially responsible for variances from the estimated production lead time. 9. Line item comments on this quotation do not pass through to manufacturing. 10. It is the customer's responsibility to ensure code and spec compliance. Building code requirements may effect changes to product and pricing.

